2S2P NR18650-35E

Battery pack

Li-ion

Nominal voltage: 7.4V
Nominal capacity: 7000mAh
Nominal energy: 51.8Wh
Max charge: 2.5A
Discharge temperature: -10°C to 60°C
Safety advice: Do not crush, heat, incenerate, short circuit or immerse. Do not charge below 0°C.

LIGHT 1777

Designed in France

2S2P NR18650-35E

Battery pack

Li-ion

Nominal voltage: 7.4V
Nominal capacity: 7000mAh
Nominal energy: 51.8Wh
Max charge: 2.5A
Discharge temperature: -10°C to 60°C
Safety advice: Do not crush, heat, incenerate, short circuit or immerse. Do not charge below 0°C.

LIGHT 1777

Designed in France

2S2P NR18650-35E

Battery pack

Li-ion

Nominal voltage: 7.4V
Nominal capacity: 7000mAh
Nominal energy: 51.8Wh
Max charge: 2.5A
Discharge temperature: -10°C to 60°C
Safety advice: Do not crush, heat, incenerate, short circuit or immerse. Do not charge below 0°C.

LIGHT 1777

Designed in France

2S2P NR18650-35E

Battery pack

Li-ion

Nominal voltage: 7.4V
Nominal capacity: 7000mAh
Nominal energy: 51.8Wh
Max charge: 2.5A
Discharge temperature: -10°C to 60°C
Safety advice: Do not crush, heat, incenerate, short circuit or immerse. Do not charge below 0°C.

LIGHT 1777

Designed in France

2S2P NR18650-35E

Battery pack

Li-ion

Nominal voltage: 7.4V
Nominal capacity: 7000mAh
Nominal energy: 51.8Wh
Max charge: 2.5A
Discharge temperature: -10°C to 60°C
Safety advice: Do not crush, heat, incenerate, short circuit or immerse. Do not charge below 0°C.

LIGHT 1777

Designed in France

2S2P NR18650-35E

Battery pack

Li-ion

Nominal voltage: 7.4V
Nominal capacity: 7000mAh
Nominal energy: 51.8Wh
Max charge: 2.5A
Discharge temperature: -10°C to 60°C
Safety advice: Do not crush, heat, incenerate, short circuit or immerse. Do not charge below 0°C.

LIGHT 1777

Designed in France

2S2P NR18650-35E

Battery pack

Li-ion

Nominal voltage: 7.4V
Nominal capacity: 7000mAh
Nominal energy: 51.8Wh
Max charge: 2.5A
Discharge temperature: -10°C to 60°C
Safety advice: Do not crush, heat, incenerate, short circuit or immerse. Do not charge below 0°C.

LIGHT 1777

Designed in France

2S2P NR18650-35E

Battery pack

Li-ion

Nominal voltage: 7.4V
Nominal capacity: 7000mAh
Nominal energy: 51.8Wh
Max charge: 2.5A
Discharge temperature: -10°C to 60°C
Safety advice: Do not crush, heat, incenerate, short circuit or immerse. Do not charge below 0°C.

LIGHT 1777

Designed in France

2S2P NR18650-35E

Battery pack

Li-ion

Nominal voltage: 7.4V
Nominal capacity: 7000mAh
Nominal energy: 51.8Wh
Max charge: 2.5A
Discharge temperature: -10°C to 60°C
Safety advice: Do not crush, heat, incenerate, short circuit or immerse. Do not charge below 0°C.

LIGHT 1777

Designed in France

2S2P NR18650-35E

Battery pack

Li-ion

Nominal voltage: 7.4V
Nominal capacity: 7000mAh
Nominal energy: 51.8Wh
Max charge: 2.5A
Discharge temperature: -10°C to 60°C
Safety advice: Do not crush, heat, incenerate, short circuit or immerse. Do not charge below 0°C.

LIGHT 1777

Designed in France

2S2P NR18650-35E

Battery pack

Li-ion

Nominal voltage: 7.4V
Nominal capacity: 7000mAh
Nominal energy: 51.8Wh
Max charge: 2.5A
Discharge temperature: -10°C to 60°C
Safety advice: Do not crush, heat, incenerate, short circuit or immerse. Do not charge below 0°C.

LIGHT 1777

Designed in France

2S2P NR18650-35E

Battery pack

Li-ion

Nominal voltage: 7.4V
Nominal capacity: 7000mAh
Nominal energy: 51.8Wh
Max charge: 2.5A
Discharge temperature: -10°C to 60°C
Safety advice: Do not crush, heat, incenerate, short circuit or immerse. Do not charge below 0°C.

LIGHT 1777

Designed in France

2S2P NR18650-35E

Battery pack

Li-ion

Nominal voltage: 7.4V
Nominal capacity: 7000mAh
Nominal energy: 51.8Wh
Max charge: 2.5A
Discharge temperature: -10°C to 60°C
Safety advice: Do not crush, heat, incenerate, short circuit or immerse. Do not charge below 0°C.

LIGHT 1777

Designed in France

2S2P NR18650-35E

Battery pack

Li-ion

Nominal voltage: 7.4V
Nominal capacity: 7000mAh
Nominal energy: 51.8Wh
Max charge: 2.5A
Discharge temperature: -10°C to 60°C
Safety advice: Do not crush, heat, incenerate, short circuit or immerse. Do not charge below 0°C.

LIGHT 1777

Designed in France

2S2P NR18650-35E

Battery pack

Li-ion

Nominal voltage: 7.4V
Nominal capacity: 7000mAh
Nominal energy: 51.8Wh
Max charge: 2.5A
Discharge temperature: -10°C to 60°C
Safety advice: Do not crush, heat, incenerate, short circuit or immerse. Do not charge below 0°C.

LIGHT 1777

Designed in France